

# Exhibit D-2

## United States Patent

[19]

[11] 3,714,396

Stambler

[45] Jan. 30, 1973

[54] GRAVITY FEED CARD TRANSPORTS  
AND READERS[76] Inventor: Leon Stambler, 534 Longacre  
Avenue, Woodmere, N.Y. 11598

[22] Filed: May 15, 1970

[21] Appl. No.: 37,751

[52] U.S. Cl. ...235/61.11 C, 179/90 CS, 194/DIG. 6,  
235/61.11 E, 235/61.11 R, 346/85[51] Int. Cl. ....G06k 13/07, G06k 7/10, H04m 1/26,  
G07f 7/02, G01d 15/14[58] Field of Search ....235/61.11 B, 61.11 E, 61.7 B;  
179/6.3 CC, 90 CL; 194/DIG. 6, 4 C, 4 G;  
250/219 D; 226/56, 130; 271/57; 346/85;  
200/46

## [56] References Cited

## UNITED STATES PATENTS

2,968,521	1/1961	Gross .....	346/85
3,527,406	9/1970	Snellman .....	235/61.11 R
3,423,037	1/1969	Good .....	226/56 X
3,243,532	3/1966	Bondune .....	200/46
3,171,020	2/1965	Lord .....	235/61.11 C
3,320,369	5/1967	Hershey .....	179/90 CL

3,328,589	6/1967	Ferguson .....	250/219 I
2,670,066	2/1954	Bruce .....	194/DIG. 6
2,792,148	5/1957	Goldenberg .....	194/DIG. 6
3,470,358	9/1969	Sallach .....	235/61.11 R
3,592,972	7/1971	Lane .....	179/90 CS

Primary Examiner—Maynard R. Wilbur

Assistant Examiner—Robert M. Kilgore

Attorney—Arthur L. Plevy

## [57] ABSTRACT

An inexpensive card transport or reader serves to move a credit card or other similar type card as an identification card or the like by means of gravitational forces along a path on a surface which may be inclined with respect to the horizontal plane. The card is alternately enabled and restrained from moving by a suitable selectively operated electromechanical assembly, such as a solenoid to enable sensing elements to respond to information printed on said card. The sensing elements are used for converting the information into electrical signals having repetition rates determined by cycling means for activating the solenoid or electromechanical assembly.

8 Claims, 9 Drawing Figures

